

Gradus & NBS Specifications

Tyreguard Primary Barrier Matting

Data Sheet: Page 1 of 1 16.12.22

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Tyreguard is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Tyreguard Primary Barrier Matting

Construction (select as required): Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

Linking strip material: Aluminium

Wiper colour: Interwoven with nylon fibres in Grey or Plain rubber

Fixing: recessed in matwell – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Tyreguard Primary Barrier Matting

Construction (select as required): Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

Linking strip material: Aluminium

Wiper colour: Interwoven with nylon fibres in Grey or Plain rubber

Total height (select as required): 12mm or 18mm

Fixing: recessed in matwell – as per manufacturers instructions

Installation accessories available:

T Bar 12 / T Bar 18: 12mm / 18mm Aluminium divider bar

UMFA12 / UMFA18 / UMFA25: 12mm / 18mm / 25mm aluminium matwell frame

FRB026: 20mm brass matwell frame

Description

Tyreguard is an ideal choice where the use of recycled materials is a key consideration. Tyreguard is constructed from 100% recycled rubber wipers and aluminium scraper linking strips which are held together with galvanised steel wires. Entirely manufactured from aeroplane tyres the rubber wipers are available either interwoven with nylon fibres in Grey or Plain rubber. When installed as a true rectangle or a square Tyreguard can be reversed to extend the product's life. For a complete matting solution Tyreguard can also be used with Boulevard secondary barrier matting.

Note: Wipers are made from 100% recycled material from aeroplane tyres, of which at least 50% is vulcanised rubber with the remainder being textile material. Due to the recycled content of the matting, there will be natural inconsistencies in the pile height and shading of the wipers. These variations should become less apparent once the product has installed for a period of time.