

NBS & Gradus Specification

ADM9 Traditional Aluminium Stair Edging

Data Sheet: Page 1 of 2 DCL/DW 160226

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for ADM9 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ

Tel: 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: ADM9 with Xtra-grip Plus insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: ADM9 with Xtra-grip insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: ADM9 with Interior Standard Finish insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: ADM9 with Interior Grained Finish insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: ADM9 with Standard Exterior insert

Material: Mill finish aluminium with glass reinforced polyester/fused alumina inserts

Insert Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

NBS & Gradus Specification

ADM9 Traditional Aluminium Stair Edging

Data Sheet: Page 2 of 2 DCL/DW 160226

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ

Tel: 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: ADM9

Gauge: Ramped Profile for use with resilient floorcoverings or no floorcovering

Tread Dimension: 50mm (overall tread including ramp: 70mm)

Riser Dimension: 55mm

Channel: Mill finished aluminium channel with single, slip-resistant insert

Profile Shape: Bullnose

Insert Type & Colour (select as required): [Insert and Channel Colour Options and LRVs | Gradus - contract interior solutions](#)

Recommended Side Trims: Side trims not recommended with ramp back profiles

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

A Range

A range of attractive and hardwearing stair edgings comprising of aluminium channels with factory bonded slip resistant inserts. Suitable for interior and exterior use (dependent on insert selected), these profiles are supplied with pre-bonded inserts and capping plugs to conceal screw heads after mechanical fixing (capping plugs for pvc inserts only). Typically used with resilient floorcoverings from all major manufacturers, aluminium stair edgings are suitable for all commercial and most industrial applications.

ADM9 incorporates a 50mm tread and 55mm riser to meet the guidance in Approved Document M (The Building Regulations 2010) and BS 8300-2:2018 to help achieve an inclusive environment in line with the Equality Act 2010. ADM9 has an insert on the tread.