

NBS & Gradus Specification

AR10 Traditional Aluminium Stair Edging

Data Sheet: Page 1 of 2 AH/DW 01.02.24

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for AR10 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ

Tel: 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: AR10 with Xtra-grip Plus Insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): Asphalt (LRV: 4.52), Shark (LRV: 5.03), Bark (LRV: 5.71), Mercury (LRV: 12.56), Smoke (LRV: 24.71), Dusk (LRV: 37.44), Air (LRV: 43.58), Prairie (LRV: 45.84), Sandstone (LRV: 46.83), Citrine (LRV: 49.97), Fossil (LRV: 43.77), Lunar (LRV: 52.79), Calcite (LRV: 66.51)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: AR10 with Xtra-grip insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Concrete (LRV: 37.44), Surf (LRV: 43.58), Bamboo (LRV: 45.84), Pumice (LRV: 46.83), Ochre (LRV: 49.97), Ivory (LRV: 43.77), Platinum (LRV: 52.79), Frost (LRV: 66.51)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: AR10 with Interior Standard Finish insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05), Midnight (LRV: 6.56), Evergreen (LRV: 6.69), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Lead (LRV: 12.77), Steel (LRV: 26.99), Cloud (LRV: 28.57), Linen (LRV: 38.59), Glacier (LRV: 42.09), Clay (LRV: 47.97), Sky (LRV: 52.63), Canvas (LRV: 53.27), Jade (LRV: 53.98), Buttercup (LRV: 55.54), Photoluminescent (LRV: 57.59), Wisp (LRV: 58.17), Snowdrift (LRV: 83.77)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: AR10 with Interior Grained Finish insert

Material: Mill finish aluminium with PVC inserts

Insert Colour (select as required): Black (LRV: 6.47), Brown (LRV: 12.13), Granite (LRV: 13.44), Dove (LRV: 23.40)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Or

Reference: AR10 with Standard Exterior insert

Material: Mill finish aluminium with glass reinforced polyester/fused alumina inserts

Insert Colour (select as required): Tornado (LRV: 4.49), Sandstorm (LRV: 50.77), Hurricane (LRV: 30.43), Blizzard (LRV: 83.25)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

NBS & Gradus Specification

AR10 Traditional Aluminium Stair Edging

Data Sheet: Page 2 of 2 AH/DW 01.02.24

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ
Tel: 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: AR10

Gauge: 2.5mm for use with resilient floorcoverings

Tread Dimension: 94mm

Riser Dimension: 51mm

Channel: Mill finished aluminium channel with double, slip-resistant inserts

Profile Shape: Bullnose

Insert Type & Colour (select as required):

Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Asphalt (LRV: 4.52), Shark (LRV: 5.03), Bark (LRV: 5.71), Mercury (LRV: 12.56), Smoke (LRV: 24.71), Dusk (LRV: 37.44), Air (LRV: 43.58), Prairie (LRV: 45.84), Sandstone (LRV: 46.83), Citrine (LRV: 49.97), Fossil (LRV: 43.77), Lunar (LRV: 52.79), Calcite (LRV: 66.51)

Or

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions) in colour:

Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Concrete (LRV: 37.44), Surf (LRV: 43.58), Bamboo (LRV: 45.84), Pumice (LRV: 46.83), Ochre (LRV: 49.97), Ivory (LRV: 43.77), Platinum (LRV: 52.79), Frost (LRV: 66.51)

Or

Interior Standard Finish insert with low risk of slip in interior dry conditions (PTV >36) in colour: Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05), Midnight (LRV: 6.56), Evergreen (LRV: 6.69), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Lead (LRV: 12.77), Steel (LRV: 26.99), Cloud (LRV: 28.57), Linen (LRV: 38.59), Glacier (LRV: 42.09), Clay (LRV: 47.97), Sky (LRV: 52.63), Canvas (LRV: 53.27), Jade (LRV: 53.98), Buttercup (LRV: 55.54), Photoluminescent (LRV: 57.59), Wisp (LRV: 58.17), Snowdrift (LRV: 83.77)

Or

Interior Grained Finish insert with low risk of slip in interior dry conditions (PTV >36) in colour: Black (LRV: 6.47), Brown (LRV: 12.13), Granite (LRV: 13.44), Dove (LRV: 23.40)

Or

Standard Exterior insert with low risk of slip in both wet and dry conditions (PTV >36 in wet and dry conditions) in colour: Tornado (LRV: 4.49), Sandstorm (LRV: 50.77), Hurricane (LRV: 30.43), Blizzard (LRV: 83.25)

Recommended Side Trim: Not applicable

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

A Range

A range of attractive and hardwearing stair edgings comprising of aluminium channels with factory bonded slip resistant inserts. Suitable for interior and exterior use (dependent on insert selected), these profiles are supplied with pre-bonded inserts and capping plugs to conceal screw heads after mechanical fixing (capping plugs for pvc inserts only). Typically used with resilient floorcoverings from all major manufacturers, aluminium stair edgings are suitable for all commercial and most industrial applications.

As with all Gradus stair edgings, AR10 helps to meet the guidance in Approved Document M (The Building Regulations 2010) and helps to achieve an inclusive environment in line with the Equality Act 2010.