

CREATION 55
LOOSELAY

gerflor.co.uk
gerflor.ie
gradus.com

Cl/SfB	(43)	Tn6	

CREATION 55 LOOSELAY

DESCRIPTION

Total Thickness	EN ISO 24346 (EN 428)	mm	4.5
Wear Layer Thickness	EN ISO 24340 (EN 429)	mm	0.55
Weight	EN ISO 23997 (EN 430)	g/m²	7500
Size	EN ISO 24342 (EN 427)	mm	229 x 1220 / 500 x 500

CLASSIFICATION

Norm / Product Specification	-	-	EN ISO 10582 (EN 649)
European Classification	EN ISO 10874 (EN 685)	Class	33-42
Fire Rating	EN 13 501-1	Class	Bfl-s1
Static Electrical Propensity	EN 1815	kV	<2
Slip Resistance Wet (ramp test with oil)	DIN 51130	Class	R10

PERFORMANCES

Wear Resistance	EN 660.2	mm³	≤2.0
Wear Group	EN 652	group	T
Type Binder Content	ISO 10582	group	I
Dimensional Stability (norm)	EN ISO 23999 (EN 434)	%	≤0.15
Residual Indentation	EN ISO 24343-1 (EN 433)	mm	≤0.10
Impact Sound Insulation	EN ISO 717-2	dB	7
Room Impact	NF S 31074	dB	73
Castor Chair Test	ISO 4918 (EN 425)	-	OK
Thermal Conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour Fastness	EN 20 105 - B02	degree	≥6
Surface Treatment	-	-	PUR+ Matt
Chemical Products Resistance	EN ISO 26987 (EN 423)	-	OK

ENVIRONMENT/INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/m³	<10
--------------------	-------------	-------	-----



IMPORTANT: The information contained in this document is valid from 01/11/2019 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

CREATION, NO FORMALDEHYDE, BETTER INDOOR AIR QUALITY

COMPOSITION
100% REACH
Phthalate Free
(except recycled content)

INDOOR AIR QUALITY
TVOC below detection level
No Formaldehyde emission

RECYCLABILITY
100%

RECYCLED CONTENT
35%

WELLNESS
Walking noise: 73dB

Distributed by:

Gradus Carpets, Park Green, Macclesfield, Cheshire, SK11 7LZ, UK
Tel: 01625 859000

