

EMPHASIS

gerflor.co.uk
gerflor.ie
gradus.com

| |
|----------------------------|
| Uniclass Pr_35_57_11_62 |
| CI/SfB (43) Tn6 |

EMPHASIS

SPECIFICATION

| | |
|------------------------|-------------------------|
| Product Format | Tile |
| Product Dimensions | 500mm x 500mm |
| Product Construction | Tufted Loop Pile |
| Surface Yarn | ECONYL® Regenerated SDN |
| Total Carpet Weight | 4200 g/m ² |
| Tufted Pile Weight | 615 g/m ² |
| Gauge | 1/10" (39.4 per dm) |
| Stitches | 37.5 per dm |
| Primary Backing | Non-woven |
| Secondary Backing | Bitumen |
| Total Carpet Thickness | 6.8mm |

PERFORMANCE SPECIFICATION

| | |
|------------------------------------|------------------|
| Classification | Heavy Commercial |
| Castor Chair BS EN 985 Test A | Pass |
| Impact Noise Reduction ISO 10140-3 | 25dB |
| Static Electricity ISO 6356 | <2kV |

FLAMMABILITY

| | |
|---------------|--------------|
| BS EN 13501-1 | Class Bfl-s1 |
|---------------|--------------|

WARRANTIES

| | |
|----------------------|---------|
| Wear Warranty | 12 Year |
| Anti-static Warranty | 10 Year |

ADDITIONAL INFORMATION

| |
|--|
| Anti-soil and stain treatment. |
| Emphasis should only be used as an accent colour to complement other product ranges. |
| Emphasis should not be used as a field colour or in areas of heavy traffic such as doorway thresholds. |

ADHESIVES

| |
|---|
| For recommended adhesives contact Technical Services. |
|---|



The information contained in this document is valid from 23/10/2023 and is subject to change at any time without notice.

Contact us to order free samples

UNITED KINGDOM:

Gerflor Flooring UK Ltd
Park Green, Macclesfield,
Cheshire, SK11 7LZ
Tel: 01625 428922
E-mail: contractuk@gerflor.com
Visit: www.gerflor.co.uk

IRELAND:

Gerflor Ltd
Ballybay Road, Co. Monaghan,
A81 YD83, Republic of Ireland
Tel: +353 (0) 42 966 1431
E-mail: gerflorirl@gerflor.com
Visit: www.gerflor.ie

