

|                               |
|-------------------------------|
| Uniclass<br>Pr_35_57_11_62/64 |
| CI/SfB<br>(43)   Tn6          |

GENUS & VOLNAY

SPECIFICATION

|                        |                     |                     |                     |
|------------------------|---------------------|---------------------|---------------------|
| Product Format         | Tile                | Broadloom           | PVC Impervious      |
| Product Dimensions     | 500mm x 500mm       | 4 metres            | 2 metres            |
| Product Construction   | Tufted Cut Pile     | Tufted Cut Pile     | Tufted Cut Pile     |
| Surface Yarn           | 100% Marquésa SD    | 100% Marquésa SD    | 100% Marquésa SD    |
| Total Carpet Weight    | 4705 g/m²           | 2366 g/m²           | 4605 g/m²           |
| Tufted Pile Weight     | 1085 g/m²           | 1085 g/m²           | 1085 g/m²           |
| Gauge                  | 1/10" (39.4 per dm) | 1/10" (39.4 per dm) | 1/10" (39.4 per dm) |
| Stitches               | 43.0 per dm         | 43.0 per dm         | 43.0 per dm         |
| Primary Backing        | Non-woven           | Woven Polypropylene | Non-woven           |
| Secondary Backing      | Bitumen             | Woven Polypropylene | PVC                 |
| Total Carpet Thickness | 9mm                 | 8mm                 | 8mm                 |

PERFORMANCE SPECIFICATION

|                                        |                  |      |      |
|----------------------------------------|------------------|------|------|
| Classification                         | Heavy Commercial |      |      |
| Static Electricity ISO 6356            | <2kV             |      |      |
| Impact Sound Insulation EN ISO 10140-3 | 23dB             | 30dB | 35dB |
| Sound Absorption ISO 354               | Class E          |      |      |

FLAMMABILITY

|               |           |
|---------------|-----------|
| BS EN 13501-1 | Class Efl |
|---------------|-----------|

WARRANTIES

|                       |         |
|-----------------------|---------|
| Wear Warranty         | 15 Year |
| Anti-static Warranty  | 10 Year |
| Stain & Fade warranty | 5 Year  |

ADHESIVES

For recommended adhesives contact Technical Services.



The information contained in this document is valid from 1/2/2024 and is subject to change at any time without notice.

Contact us to order free samples

UNITED KINGDOM:  
Gerflor Flooring UK Ltd  
Park Green, Macclesfield,  
Cheshire, SK11 7LZ  
Tel: 01625 428922  
E-mail: contractuk@gerflor.com  
Visit: www.gerflor.co.uk

IRELAND:  
Gerflor Ltd  
Ballybay Road, Co. Monaghan,  
A81 YD83, Republic of Ireland  
Tel: +353 (0) 42 966 1431  
E-mail: gerflorirl@gerflor.com  
Visit: www.gerflor.ie

