

LAFITE CONNECT

gerflor.co.uk
gerflor.ie
gradus.com

Uniclass Pr_35_57_11_62
CI/SfB (43) Tn6

LAFITE CONNECT

SPECIFICATION

Product Format	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Loop Pile
Surface Yarn	100% Aquafil Solution Dyed Nylon
Total Carpet Weight	4415 g/m ²
Tufted Pile Weight	540 g/m ²
Gauge	1/10" (39.4 per dm)
Stitches	43.3 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	5.9mm

PERFORMANCE SPECIFICATION

Classification BS EN 1307	Class 33
Castor Chair BS EN 985 Test A	Pass
Static Electricity ISO 6356	<2kV
Impact Sound Insulation EN ISO 10140-3	22dB

FLAMMABILITY

BS EN 13501-1	Class Bfl-s1
---------------	--------------

WARRANTIES

Wear Warranty	10 Year
Anti-static Warranty	10 Year

ADHESIVES

For recommended adhesives contact Technical Services.







The information contained in this document is valid from 1/12/2022 and is subject to change at any time without notice.

Contact us to order free samples

UNITED KINGDOM:
Gerflor Flooring UK Ltd
Park Green, Macclesfield,
Cheshire, SK11 7LZ
Tel: 01625 428922
E-mail: contractuk@gerflor.com
Visit: www.gerflor.co.uk

IRELAND:
Gerflor Ltd
Ballybay Road, Co. Monaghan,
A81 YD83, Republic of Ireland
Tel: +353 (0) 42 966 1431
E-mail: gerflorirl@gerflor.com
Visit: www.gerflor.ie

