

Cleaning & Maintenance Guidelines

Mono-Clip System Floor Trims

Data Sheet: Page 1 of 1 AH/NF 01.09.21

The guidelines below have been compiled to help the user obtain optimum performance and satisfaction from their selected product.

They apply to the following Gradus profiles only:

KC558 / MCB554 and KC558 / MCB555

KA556 / MCB554 and KA556 / MCB555

KB557 / MCB554 and KB557 / MCB555

Preventative Maintenance Programme

A regular scheduled maintenance programme should be employed to prevent the build-up of dirt and grease, which will reduce the anti-slip properties of the profile and detract from the overall appearance of the product.

Daily Cleaning

Brush down the profiles using a soft bristled brush and remove dust particles by wiping with a damp cloth.

Twice Weekly or as Required

Brush down, using a soft bristled brush. With clean warm water, apply a small amount of a mild detergent to a lint free cloth and gently clean the surface. During the clean, the water must be changed on a regular basis. Once the profile has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.

The area should not be trafficked until the profile is completely dry.

Floor sealants, polishes or such coating should not, under any circumstances, be applied to floor trims.

If any further information is required, please do not hesitate to contact Gradus Technical Services on (+44)1625 428922.