

### NBS & Gradus Specification

---

**ETR307F0 Multi-Purpose Trim**

Data Sheet: Page 1 of 1 AH/DW 07.02.24

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for ETR307F0 shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

#### NBS Specification

**M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING  
70 EDGINGS/COVER STRIPS / 740 EDGINGS/COVER STRIPS /**

**M51 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING  
510 EDGINGS/COVER STRIPS**

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ  
**Tel:** 01625 428922 **Website:** [www.gradus.com](http://www.gradus.com) **Email:** [sales@gradus.com](mailto:sales@gradus.com)

**Reference:** ETR307F0

**Material:** Natural Aluminium

**Fixing:** Bed into adhesive at the same time as tiling – as per manufacturers instructions. Profiles are supplied with pre-punched fixing tabs and holes on the flange to allow curves on-site for edges and inlays.

#### Gradus Detailed Specification

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ  
**Tel:** 01625 428922 **Website:** [www.gradus.com](http://www.gradus.com) **Email:** [sales@gradus.com](mailto:sales@gradus.com)

**Reference:** ETR307F0

**Height:** 7.5mm

**Gauge:** 6mm

**Width:** 22.5mm

**Length:** Available in 2.50m or 2.715m

**Material:** Natural Aluminium

**Curving radius:** 400mm

**Fixing:** Bed into adhesive at the same time as tiling – as per manufacturers instructions. Profiles are supplied with pre-punched fixing tabs and holes on the flange to allow curves on-site for edges and inlays.

#### Description

##### Multi-Purpose Trims

Gradus Multi-Purpose Trims are designed to be used as a transition trim between different types of flooring, allowing quick and easy installation of tiles regardless of tile thickness. They are designed for installation with tiles but are also suitable for use with other types of flooring such as marble, stone, wood, industrial resin floors and natural stone.