

These instructions apply to the following Gradus aluminium profiles only:

|  |  |
|--|--|
| <b>Product Codes</b><br><i>(suppliers product codes)</i> | <b>ALS/B/1 &amp; ALS/B/2</b> (P-B-1 & P-B-2)<br><b>ALS/DR/1 &amp; ALS/DR/2</b> (P-DR-1 & P-DR-2)<br><b>ALS/DS/1 &amp; ALS/DS/2</b> (P-DS-1 & P-DS-2)<br><b>ALS/FB/1</b> (P-FB-1)<br><b>ALS/FC/1 &amp; ALS/FC/2</b> (P-C-1 & P-C-2)<br><b>ALS/FR/2</b> (P-FR-2)<br><b>ALS/OL/1 &amp; ALS/OL/2</b> (P-OL-1 & P-OL-2)<br><b>ALS/SR/1 &amp; ALS/SR/2</b> (P-SR-1 & P-SR-2)<br><b>ALS/TS/1 &amp; ALS/TS/2</b> (P-TS-1 & P-TS-2)<br><b>ALS/WO/1 &amp; ALS/WO/2</b> (P-WO-1 & P-WO-2) |
|--|--|

Aluminium profiles can accumulate dust and dirt over time. The cover therefore requires cleaning to keep maximum light output and true colour effect.

Please follow the instructions below:

1. Before you begin, you must ensure that the LED strips are switched off.
2. Remove the diffuser cover from the base. This can be wiped on both sides with a damp cloth.
1. The base of the profile must only be wiped with a dry cloth to avoid any water damage to the LED strips.
2. It is important to ensure that the diffuser cover is completely dry before clipping it back into the base.