

Gradus & NBS Specifications

Access 6000 Hybrid Barrier Matting

Data Sheet: Page 1 of 1 KB_LB 03.07.2018

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Access 6000 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Access 6000 Hybrid Barrier Matting

Construction (select as required): Closed construction, 12mm or 17mm height

Rubber base colour (select as required): Black, Grey

Wiper colour (select as required): Swallow, Walnut, Rosemary, Galaxy, Indigo, Atlantic, Nickel, Nightfall

Fixing: recessed in matwell or surface mounted with ramping frame – as per manufacturer's instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Access 6000 Hybrid Barrier Matting

Module construction: Rubber base incorporating carpet wipers

Construction: Closed

Wiper material: ECONYL® Regenerated Solution Dyed Nylon

Total height (including carpet pile) (select as required): 12mm or 17mm

Rubber base colour (select as required): Black, Grey

Wiper colour (select as required): Swallow, Walnut, Rosemary, Galaxy, Indigo, Atlantic, Nickel, Nightfall

Fixing: recessed in matwell or surface mounted with ramping frame – as per manufacturer's instructions

Installation accessories available:

UMFA12 / UMFA18 / UMFA25: 12mm / 18mm / 25mm aluminium matwell frames

FRA031: 25mm aluminium matwell frame

FRB026: 25mm brass matwell frame

RAM012: 12mm pvc ramping frame

SPA012 / SPA017: 12mm / 17mm PVC spacer strips

Description

Access 6000 is a modular hybrid barrier mat suitable for smaller areas of medium foot traffic and light wheeled traffic. The mat is a moulded solid synthetic rubber unit available in either Grey or Black with a choice of ECONYL® regenerated solution dyed nylon wipers and is available in 17mm and 12mm thicknesses.

The 17mm mat is usually recessed into a matwell whereas the 12mm version can be surface mounted using the 12mm ramping profile. Modules are 2000mm wide x 500mm deep and are supplied oversize for trimming in on site. Access is supplied with appropriate compression strips to allow for small movements as a result of changes in ambient temperature. Access 6000 can be used in conjunction with Boulevard 6000 secondary barrier matting to provide a fully co-ordinated system.