

Boulevard 1500

Barrier Matting

Uniclass
Pr_35_57_11_26
Cl/SfB
(43) Tn6

A cost effective barrier matting that is easy to install and maintain. Its ribbed design is resistant to compression and offers a superior alternative to coir matting, in line with the guidance in BS 8300-2:2018 and Approved Document M of The Building Regulations 2010.

Barrier carpet provides an effective solution to reducing maintenance costs on surrounding floorcoverings and helps minimise the risk of slip on hard floor finishes. It can also, when maintained correctly, help protect the appearance of surrounding floorcoverings throughout their life. Boulevard 1500 is often used in conjunction with a primary entrance mat and in some situations can be used as a stand alone matting in entrances and access points.

Designed to complement Esplanade 1500 primary barrier matting.

Boulevard 1500

Specification

Product Format	Sheet
Product Dimensions	15m x 2m
Product Construction	Needlepunch
Surface Yarn	100% Polypropylene
Total Carpet Weight	2600 g/m ²
Tufted Pile Weight	1700 g/m ²
Backing	Rubber
Total Carpet Thickness	10mm

Performance Specification

Static Electricity ISO 6356	<2kV
-----------------------------	------

Flammability

BS EN 13501-1	Class Efl-s1
---------------	--------------

Warranties

Wear Warranty	5 Year
---------------	--------

Adhesives

For recommended adhesives contact Technical Services on 01625 428922
--



The information contained in this document is valid from 1/7/2024 and is subject to change at any time without notice.

Contact us to order free samples

Gradus Ltd Park Green Macclesfield Cheshire SK11 7LZ

For enquiries outside the UK and Eire
contact Gradus International on +44 (0)1625 613780

call: 01625 428922
visit: www.gradus.com

GRADUS