

Gradus & NBS Specifications

Boulevard 6000 Secondary Barrier Matting

Data Sheet: Page 1 of 1 19.01.22

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Boulevard 6000 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 6000 Secondary Barrier Matting

Colour (select as required): Atlantic (LRV: 1.90) Galaxy (LRV: 2.56), Indigo (LRV: 4.01), Nickel (LRV: 3.70), Nightfall (LRV: 1.48), Rosemary (LRV: 4.45), Shadow (LRV: 5.36), Walnut (LRV: 2.86)

Fixing: adhesive – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 6000 Secondary Barrier Matting

Product construction: Tufted Cut Pile

Surface yarn: ECONYL® Regenerated SDN

Dimensions / backing: Broadloom: Roll 2m x 25m, pvc, non-woven primary backing; Tile: 500mm x 500mm, bitumen, non-woven primary backing

Tufted pile weight: 950g/m²

Total carpet thickness: Broadloom – 8mm; Tile - 9mm

Total carpet weight: 4750g/m²

Colour (select as required): Atlantic (LRV: 1.90) Galaxy (LRV: 2.56), Indigo (LRV: 4.01), Nickel (LRV: 3.70), Nightfall (LRV: 1.48), Rosemary (LRV: 4.45), Shadow (LRV: 5.36), Walnut (LRV: 2.86)

Performance Specification

Classification – BS EN 1307: Class 3

Static Electricity - ISO 6356: <2kV

Thermal Resistance – BS 4745:1990: 1.3 (TOG)

Flammability

Fire rating – BS EN 13501-1: Broadloom – Class Cfl-s1; Tile – Class Bfl-s1

Warranty: 10 years wear warranty

Fixing: adhesive – as per manufacturers instructions

Description

Boulevard 6000 is a high performance secondary barrier carpet, offering excellent scraping and moisture retention properties. Ideal for use in all areas of a building, particularly those at greatest risk of damage from tracked through soil and moisture, e.g. kitchens, lifts etc. In some situations, Boulevard 6000 can be used as stand-alone matting in entrances and access points. Boulevard 6000 is designed to complement Esplanade 6000 primary barrier matting and Access 6000 and Mat-in-a-Box 6000 hybrid barrier matting.