

# Boulevard 6000

Uniclass Pr_35_57_11_26
CI/SfB (43) Tn6

## Product information:

Boulevard 6000 is constructed from ECONYL® regenerated solution dyed nylon yarn and incorporates a heavy scraper fibre for optimum dirt removal and moisture retention. The range is available in a choice of eight colours in either sheet or tile format.

Barrier matting provides an effective solution to reducing maintenance costs on surrounding floorcoverings and helps minimise the risk of slip on hard floor finishes. It can also, when maintained correctly, help protect the appearance of surrounding floorcoverings throughout their life.

Boulevard 6000 can be used in conjunction with a primary entrance mat and in some situations can be used as stand-alone matting in entrances and access points. It is also ideal for use in any area of a building prone to soil and moisture damage such as staircases, lifts and canteen areas or in areas of heavy wear such as reception areas and corridors.

The range is designed to complement Mat-in-a-Box 6000, Access 6000 and Esplanade 6000.

## Warranties:

10 year wear warranty  
Full warranty details available on request



Environmental Profiles  
Cert No. ENP 399

**BRE Global (BREEAM):**  
For specific ratings visit: [www.greenbooklive.com](http://www.greenbooklive.com)

## Specification:

Product Form	Tile	Sheet
Product Dimensions .....	500mm x 500mm	25m x 2m
Product Construction .....	Tufted Cut Pile	Tufted Cut Pile
Surface Yarn .....	ECONYL® Regenerated SDN	ECONYL® Regenerated SDN
Total Carpet Weight .....	4750 g/m <sup>2</sup>	4750 g/m <sup>2</sup>
Tufted Pile Weight .....	950 g/m <sup>2</sup>	950 g/m <sup>2</sup>
Primary Backing .....	Non-woven	Non-woven
Secondary Backing .....	Bitumen	Pvc
Total Carpet Thickness .....	9mm	8mm
Pile Height .....	5mm	5mm
<b>Performance Specification</b>		
Classification BS EN 1307 .....	Class 3	Class 3
Static Electricity ISO 6356 .....	<2kV	<2kV
Thermal Resistance BS 4745: 1990 .....	-	1.3 (TOG)
<b>Flammability</b>		
BS EN 13501-1 .....	Class Bfl-s1	Class Cfl-s1

For recommended adhesives contact Technical Services on 01625 428922.



FM 10763



EMS 59511



BS OHSAS  
18001:2007  
IV 18/18493

# GRADUS

Gradus Accessories Park Green Macclesfield Cheshire SK11 7LZ UK Tel: 01625 428922

For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

[www.gradus.com](http://www.gradus.com)