

Data Sheet: Page 1 of 1 DLC 05/11/2024

## **Gradus NBS Specification**

#### **Boulevard 7000 Secondary Barrier Matting**

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Boulevard 7000 is shown below, plus a detailed Gradus specification and profile description to

the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

#### **NBS Specification**

# N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 7000 Secondary Barrier Matting

Colour (select as required): Black Ash (LRV: 3.06), Gray Birch (LRV: 5.60), Hazelnut (LRV: 2.37), Red Oak (LRV: 1.98)

Fixing: adhesive – as per manufacturers instructions

#### **Gradus Detailed Specification**

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 7000 Secondary Barrier Matting

**Product construction:** Tufted Cut Pile **Surface yarn:** 100% Solution Dyed Nylon

Dimensions / backing: +/- 20m x 2m, non-woven Polyester/Polyamide

Tufted pile weight: +/- 825g/m2 Total carpet thickness: +/- 8mm Total carpet weight: +/- 3525g/m2

Colour (select as required): Black Ash (LRV: 3.06), Gray Birch (LRV: 5.60), Hazelnut (LRV: 2.37), Red Oak (LRV: 1.98)

#### **Performance Specification**

Classification – BS EN 1307: Class 33 Static Electricity - ISO 6356: <2kV

#### Flammability

Fire rating - BS EN 13501-1: Class Cfl-s1

Warranty: 10 years wear warranty

Fixing: adhesive – as per manufacturers instructions

### **Description**

Boulevard 7000 is constructed from 100% solution dyed nylon yarn and incorporates a heavy scraper fibre for optimum dirt removal and moisture retention. The range is available in a choice of four colours in sheet format. Boulevard 7000 can be used in conjunction with a primary entrance mat and in some situations can be used as stand-alone matting in entrances and access points. It is also ideal for use in areas of a building prone to soil and moisture damage such as lifts and canteen areas or in areas of heavy wear such as reception areas or corridors

Gradus Limited Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 428922 Fax: 01625 433949 For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780