

Cleaning and Maintenance Information

Primary Barrier Matting

Data Sheet: Page 1 of 2 CD 29.08.18

This leaflet has been compiled to help the user obtain optimum performance and satisfaction from their selected product:

To maintain the performance and visual appearance of Gradus Barrier Matting Systems and to maximise the lifespan of the products, a regular cleaning and maintenance programme is crucial.

Daily Cleaning

Sweep and vacuum daily to remove surface soil using a heavy duty upright vacuum cleaner with a brush or tub vacuum cleaner with a power head. Inspect for chewing gum and remove as necessary (see below for more information on chewing gum removal).

If the matting is wet, the area should be vacuumed using a wet pick up vacuum to remove as much water / soil as possible.

Deep Cleaning

To maintain a good visible standard, the matting will require deep cleaning on a weekly / monthly / as required basis (depending on weather conditions and volume of traffic). Deep cleaning can be carried out using various methods, depending on equipment availability.

In all cases, deep cleaning must follow brushing and vacuuming. Attention must be given to stains by using a pretreatment of Spot & Stain carpet remover and chewing gum remover if required.

- A) Preferred Method: the use of a conventional jet extraction carpet machine, using a conventional floor tool with vigour, scrubbing the carpet wipers and continuing to extract as much water as possible. This method leaves the carpet as dry as possible.
- B) Alternative Method: a solution of the carpet cleaner may be applied by deck scrubber and removed by a wet pick up machine. This is a very physical operation and will require some effort. A number of applications may also be required.
- C) Deeply Soiled Matting: it is advised to carry out the initial steps of pre-cleaning but then apply the carpet solution via a rotary scrubbing machine fitted with a shampoo brush, scrubbing the carpet surface and removing the soiled solution by a wet pick up machine or a jet extraction machine. Either machine can then be used to rinse the matting with clean water.

Periodic Maintenance

Where possible, the mat should be lifted and the matwell cleaned to remove soil and debris.

Chewing Gum Removal

NOTE: Always follow Selden's instructions for use. Test a small inconspicuous area of the carpet for colour fastness before commencing cleaning. Spray liberally over the chewing gum and immediate surrounding area. Wait for a few minutes for the chemical action to take place. Using a blunt edged scraper and/or cloth - gently peel the gum from the carpet, taking care not to damage delicate fabrics. After use rinse out with water or a suitable extraction shampoo using an extraction machine.

Recommended Cleaning Product

Product Description	Name of Cleaner	Code
Chewing Gum Remover	D-Bond	T133

Gradus Limited Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 428922 Fax: 01625 433949 For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

Accessories



Cleaning and Maintenance Information

Primary Barrier Matting Data Sheet: Page 2 of 2 CD 29.08.18

Recommended Cleaning Products for Gradus Barrier Matting

Gradus has worked with Selden Research to undertake extensive testing on Gradus barrier matting products. As a result, a range of cleaning products have been recommended for use with Gradus matting.

For further information about these cleaning products, including instructions for use and COSHH data sheets, please contact: Selden Research Limited, Staden Business Park, Staden Lane, Buxton, Derbyshire, SK17 9RZ.

Tel: 01298 26226

Email: gradus@selden.co.uk
Web: www.selden.co.uk

Product Description	Name of Cleaner	Code
High Soiling & Traffic Cleaner	Heavy Duty Extraction Shampoo	C156
Hot Water Extraction Cleaner	Selfoam H.E.	C034
Carpet Spot & Stain Remover	Spot & Stain	T012