

NBS & Gradus Specification

RNRC551 PVC-u Hardnose Stair Edging - Satin Finish

Data Sheet: Page 1 of 2 AH/DW 07.02.24

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for RNRC551 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: RNRC551 with Xtra-grip Plus Insert

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Ink (LRV: 5.40), Granite (LRV: 11.69), Glacier (LRV: 42.73), Buttercup (LRV: 62.62)

Insert Colour: Asphalt (LRV: 4.52), Shark (LRV: 5.03), Bark (LRV: 5.71), Mercury (LRV: 12.56), Smoke (LRV: 24.71), Dusk (LRV: 37.44), Citrine (LRV: 49.97), Air (LRV: 43.58), Sandstone (LRV: 46.83), Prairie (LRV: 45.84), Calcite (LRV: 66.51)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

or

Reference: RNRC551 with Xtra-grip Insert

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Ink (LRV: 5.40), Granite (LRV: 11.69), Glacier (LRV: 42.73), Buttercup (LRV: 62.62)

Insert Colour: Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Concrete (LRV: 37.44), Ochre (LRV: 49.97), Surf (LRV: 43.58), Pumice (LRV: 46.83), Bamboo (LRV: 45.84), Frost (LRV: 66.51)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

or

Reference: RNRC551 with Interior Insert/ Interior Insert - Grained

Material: PVC-u channel with PVC insert

Channel Colour: Black (LRV: 4.99), Ink (LRV: 5.40), Granite (LRV: 11.69), Glacier (LRV: 42.73), Buttercup (LRV: 62.62)

Insert Colour: Interior Insert: Jet (LRV: 4.56), Ink (LRV: 4.96), Midnight (LRV: 6.56), Burgundy (LRV: 5.70), Evergreen (LRV: 6.69), Coffee (LRV: 6.05), Ocean (LRV: 8.00), Lead (LRV: 12.77), Cloud (LRV: 28.57), Steel (LRV: 26.99), Linen (LRV: 38.59), Glacier (LRV: 42.09), Canvas (LRV: 53.27), Buttercup (LRV: 55.54), Poppy (LRV: 10.39), Photoluminescent (LRV: 57.59), Snowdrift (LRV: 83.77) or Interior Insert – Grained: Black (LRV: 6.47), Brown (LRV: 12.13), Granite (LRV: 13.44), Dove (LRV: 23.40)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

NBS & Gradus Specification

RNRC551 PVC-u Hardnose Stair Edging - Satin Finish

Data Sheet: Page 2 of 2 AH/DW 07.02.24

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: RNRC551

Gauge: Ramp back

Tread Dimension: 71mm

Riser Dimension: 34mm

Channel: Single PVC-u channel with slip-resistant PVC insert

Profile Shape: Rake back

Channel Colour: Black (LRV: 4.99), Ink (LRV: 5.40), Granite (LRV: 11.69), Glacier (LRV: 42.73), Buttercup (LRV: 62.62)

Insert Type & Colour (select as required):

Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Asphalt (LRV: 4.52), Shark (LRV: 5.03), Bark (LRV: 5.71), Mercury (LRV: 12.56), Smoke (LRV: 24.71), Dusk (LRV: 37.44), Citrine (LRV: 49.97), Air (LRV: 43.58), Sandstone (LRV: 46.83), Prairie (LRV: 45.84), Calcite (LRV: 66.51)

or

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions)) in colour: Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Concrete (LRV: 37.44), Ochre (LRV: 49.97), Surf (LRV: 43.58), Pumice (LRV: 46.83), Bamboo (LRV: 45.84), Frost (LRV: 66.51)

or

Interior Insert / Interior Insert – Grained with low risk of slip in interior dry conditions (PTV 68). Interior Insert in colour: Jet (LRV: 4.56), Ink (LRV: 4.96), Midnight (LRV: 6.56), Burgundy (LRV: 5.70), Evergreen (LRV: 6.69), Coffee (LRV: 6.05), Ocean (LRV: 8.00), Lead (LRV: 12.77), Cloud (LRV: 28.57), Steel (LRV: 26.99), Linen (LRV: 38.59), Glacier (LRV: 42.09), Canvas (LRV: 53.27), Buttercup (LRV: 55.54), Poppy (LRV: 10.39), Photoluminescent (LRV: 57.59), Snowdrift (LRV: 83.77) **or** Interior Insert – Grained: Black (LRV: 6.47), Brown (LRV: 12.13), Granite (LRV: 13.44), Dove (LRV: 23.40)

Recommended Side Trims: Not applicable

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

RNRC range

A range of attractive and hardwearing stair edgings comprising of PVC-u channels with slip resistant inserts. Suitable for interior use, RNRC profiles feature an extended insert design to provide additional slip-resistance around the leading edge of the stair edging. Typically used with resilient floorcoverings from all major manufacturers, profiles are suitable for applications such as commercial office, retail and healthcare.

As with all Gradus stair edgings RNRC551 helps to meet the guidance in Approved Document M (The Building Regulations 2010) and helps to achieve an inclusive environment in line with the Equality Act 2010.