

Gradus & NBS Specifications

DDXT1 Aluminium Stair Edging

Data Sheet: Page 1 of 2 LB/02.04.18

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for DDXT1 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.
Tel: 01625 428922 Fax: 01625 433939
Website: www.gradus.com Email: sales@gradus.com

Reference: DDXT1 with Xtra-grip Plus Insert

Material: PVC-u channel with pvc insert

Channel Colour: Black (LRV: 4.99), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54), Burgundy (LRV: 5.89), Clay (LRV: 51.53), Jade (LRV: 55.54), Sky (LRV: 55.38), Wisp (56.62) (select as required)

Insert Colour: Asphalt (LRV: 4.52); Shark (LRV: 5.03); Bark (LRV: 5.93); Mercury (LRV: 12.56); Smoke (LRV: 24.71); Dusk (LRV: 37.44); Sandstone (LRV: 46.83); Citrine (LRV: 49.97); Air (LRV: 43.58); Prairie (LRV: 45.84); Calcite (LRV: 66.51) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
Or

Reference: DDXT1 with Xtra-grip Insert

Material: PVC-u channel with pvc insert

Channel Colour: Black (LRV: 4.99), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54), Burgundy (LRV: 5.89), Clay (LRV: 51.53), Jade (LRV: 55.54), Sky (LRV: 55.38), Wisp (56.62) (select as required)

Insert Colour: Onyx (LRV: 4.52); Neptune (LRV: 5.03); Umber (LRV: 5.71); Graphite (LRV: 12.56); Quarry (LRV: 24.71); Concrete (LRV: 37.44); Pumice (LRV: 46.83); Ochre (LRV: 49.97); Surf (LRV: 43.58); Bamboo (LRV: 45.84); Frost (LRV: 66.51) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions
Or

Reference: DDXT1 with Interior Insert

Material: PVC-u channel with pvc insert

Channel Colour: Black (LRV: 4.99), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54), Burgundy (LRV: 5.89), Clay (LRV: 51.53), Jade (LRV: 55.54), Sky (LRV: 55.38), Wisp (56.62) (select as required)

Insert Colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Coffee (LRV: 6.05), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Clay (LRV: 47.97), Sky (LRV: 52.63), Jade (LRV: 53.98), Wisp (LRV: 58.17) (select as required)

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Gradus & NBS Specifications

DDXT1 Aluminium Stair Edging

Data Sheet: Page 2 of 2 LB/02.04.18

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: DDXT1

Gauge: 4mm

Tread Dimension: 55mm

Riser Dimension: 55mm

Channel: Single PVC-u channel with slip-resistant pvc insert

Profile Shape: Square

Channel Colour select as required: Black (LRV: 4.99), Brown (LRV: 7.15), Buttercup (LRV: 62.62), Canvas (LRV: 55.43), Dove (LRV: 26.19), Glacier (LRV: 42.73), Granite (LRV: 11.69), Ink (LRV: 5.40), Snowdrift (LRV: 80.54), Burgundy (LRV: 5.89), Clay (LRV: 51.53), Jade (LRV: 55.54), Sky (LRV: 55.38), Wisp (56.62)

Insert Type & Colour (select as required):

Xtra-grip Plus insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions), suitable for areas subject to regular cleaning such as catering and food preparation environments) in colour: Asphalt (LRV: 4.52); Shark (LRV: 5.03); Bark (LRV: 5.93); Mercury (LRV: 12.56); Smoke (LRV: 24.71); Dusk (LRV: 37.44); Sandstone (LRV: 46.83); Citrine (LRV: 49.97); Air (LRV: 43.58); Prairie (LRV: 45.84); Calcite (LRV: 66.51)

or

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions) in colour: Onyx (LRV: 4.52); Neptune (LRV: 5.03); Umber (LRV: 5.71); Graphite (LRV: 12.56); Quarry (LRV: 24.71); Concrete (LRV: 37.44); Pumice (LRV: 46.83); Ochre (LRV: 49.97); Surf (LRV: 43.58); Bamboo (LRV: 45.84); Frost (LRV: 66.51)

or

Interior Insert (Standard) with low risk of slip in interior dry conditions (PTV >36) in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Coffee (LRV: 6.05), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), Clay (LRV:47.97), Sky (LRV:52.63), Jade (LRV:53.98), Wisp (LRV:58.17)

Recommended Side Trim: HXT42

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

XT Hardnose Range

A range of PVC-u stair edgings incorporating an extended insert that continues around the leading edge of the profile to ensure that contact is always made with the slip-resistant element of the stair edging in line with the latest recommendations from BS 8300-2:2018 and research undertaken by BRE (Information Paper 15/03).

Selecting the channel and insert in the same colour provides the ideal solution for creating a single solid band of colour, that contrasts with the surrounding floorcovering, to define the step edge in line with Approved Document M (The Building Regulations 2010) and BS 8300-2:2018 guidelines.

Typically used with heavy resilient flooring and carpet, DDXT1 incorporates a 55mm tread and 55mm riser to meet the guidance in Approved Document M (The Building Regulations 2010) and BS 8300-2:2018 to help achieve an inclusive environment in line with the Equality Act 2010.