

NBS & Gradus Specifications

RXT581 – PVC-u Hardnose™ XT stair edging

Data Sheet: Page 1 of 2 AH/DW 26.08.2021

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for RXT581 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER / PLASTICS / CORK / LINO / CARPET TILING / SHEETING

75 / 750 / 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: RXT581 with Xtra-grip insert

Material: PVC-u channel with pvc insert

Channel Colour (select as required): Black (LRV: 4.99), Ink (LRV: 5.40), Burgundy (LRV: 5.89), Brown (LRV: 7.15), Granite (LRV: 11.69), Dove (LRV: 26.19), Glacier (LRV: 42.73), Clay (LRV: 51.53), Sky (LRV: 55.38), Canvas (LRV: 55.43), Jade (LRV: 55.54), Wisp (LRV: 56.62) Buttercup (LRV: 62.62), Snowdrift (LRV: 80.54).

Insert Colour (select as required): Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Concrete (LRV: 37.44), Surf (LRV: 43.58), Bamboo (LRV: 45.84), Pumice (LRV: 46.83), Ochre (LRV: 49.97), Frost (LRV: 66.51).

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions.

Or

Reference: RXT581 with Interior Standard Finish insert

Material: PVC-u channel with pvc insert

Channel Colour (select as required): Black (LRV: 4.99), Ink (LRV: 5.40), Burgundy (LRV: 5.89), Brown (LRV: 7.15), Granite (LRV: 11.69), Dove (LRV: 26.19), Glacier (LRV: 42.73), Clay (LRV: 51.53), Sky (LRV: 55.38), Canvas (LRV: 55.43), Jade (LRV: 55.54), Wisp (LRV: 56.62) Buttercup (LRV: 62.62), Snowdrift (LRV: 80.54).

Insert Colour (select as required): Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05), Lead (LRV: 12.77), Steel (LRV: 26.99), Glacier (LRV: 42.09), Clay (LRV: 47.97), Sky (LRV: 52.63), Canvas (LRV: 53.27), Jade (LRV: 53.98), Buttercup (LRV: 55.54), Wisp (LRV: 58.17), Snowdrift (LRV: 83.77).

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions.

NBS & Gradus Specifications

RXT581 – PVC-u Hardnose™ XT stair edging

Data Sheet: Page 2 of 2 AH/DW 26.08.2021

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: RXT581

Gauge: 4.5mm - typically used with carpet or resilient flooring with bevelled underlay in heavy use areas

Tread Dimension: 58.5mm

Riser Dimension: 40mm

Channel: PVC-u channel with single, slip-resistant pvc insert

Profile Shape: Bullnose

Channel Colour (select as required):

Black (LRV: 4.99), Ink (LRV: 5.40), Burgundy (LRV: 5.89), Brown (LRV: 7.15),

Granite (LRV: 11.69), Dove (LRV: 26.19), Glacier (LRV: 42.73), Clay (LRV: 51.53), Sky (LRV: 55.38), Canvas (LRV: 55.43),

Jade (LRV: 55.54), Wisp (LRV: 56.62) Buttercup (LRV: 62.62), Snowdrift (LRV: 80.54).

Insert Type & Colour (select as required):

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions) in colour:

Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71),

Concrete (LRV: 37.44), Surf (LRV: 43.58), Bamboo (LRV: 45.84), Pumice (LRV: 46.83), Ochre (LRV: 49.97),

Frost (LRV: 66.51).

Or

Interior Standard Finish insert with low risk of slip in interior dry conditions (PTV >36) in colour:

Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05), Lead (LRV: 12.77), Steel (LRV: 26.99),

Glacier (LRV: 42.09), Clay (LRV: 47.97), Sky (LRV: 52.63), Canvas (LRV: 53.27), Jade (LRV: 53.98), Buttercup (LRV: 55.54),

Wisp (LRV: 58.17), Snowdrift (LRV: 83.77).

Recommended Side Trim: HXT42

Fixing: Gradus Grip (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

Description

PVC-u Hardnose™ XT range:

A range of PVC-u stair edgings incorporating an extended insert that continues around the leading edge of the profile to ensure that contact is always made with the slip resistant element of the stair edging in line with the latest research undertaken by BRE (Information Paper 15/03). Insert is mechanically locked in to place to provide added resistance to cleaning regimes.