

### Cleaning and Maintenance Information

---

#### Aluminium Metal Skirting

Data Sheet: Page 1 of 1 15.05.18

This information applies to the following Gradus profiles:  
(MAS90/10SF, MAS90/8SF, MAS90/6SF)

This leaflet has been compiled to help the user obtain optimum performance and satisfaction from their selected product:

#### Preventative Maintenance Programme

A regular scheduled maintenance programme should be employed to prevent the build up of dirt and grease, which will detract from the overall appearance of the product.

#### Daily Cleaning

Brush down the profiles using a soft bristled brush and remove dust particles by wiping with a damp cloth.

#### Aluminium Profile

Stubborn marks such as boot blacking may be removed from the aluminium profile by means of a green scotch pad and neutral detergent.

#### Twice Weekly or as Required

With clean, hand warm water, containing the correct dilution ratio of ph neutral cleaning solution apply a small amount to a wet green scotch pad and gently clean the surface of the skirting in a left to right motion. During the clean, the water must be changed on a regular basis. **Do not** soak the profile. Once the profile has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.

The following should not be used to clean aluminium skirtings:

- Acid or alkaline detergents
- Abrasive products or materials
- Solvents

Detergents should not be applied directly to the surface of the profile and the profile surface should not exceed 30°C or be exposed to direct sunlight.

If any further information is required, please contact Gradus Technical Support on +44 (0)1625 428922