

Installation Guidelines

Metal Skirtings

Data Sheet: Page 1 of 1 AH/KO 01.10.20

This information applies to the following Gradus profiles:

MAS90 Aluminium Skirtings: MAS90/10SF, MAS90/8SF, MAS90/6SF

MSS790 Stainless Steel Skirtings: MSS790/8SF, MSS790/6SF

MAS95 Aluminium Interlocking Skirtings: MAS95/10SF, MAS95/7SF

MAS97 Aluminium Interlocking Skirting: MAS97/8SF

Please read the following instructions prior to installation:

1. Ensure the substrate is dry, smooth and free from contaminants. Where a substrate is dusty it may be necessary to prime with a suitable primer.
2. Remove any protective film from the surface of the skirting. For MAS95 and MAS97 Interlocking Skirtings, also remove the brackets from the packaging (3 per 2m length) and fix to the wall using suitable fixing for the substrate.
3. Measure and cut the skirting to the required length using a proprietary blade for the material and cutting tool used.
4. Apply Gradus Grip (or other suitable cartridge adhesive) to the back of the **skirting for MAS90 & MSS790 profiles** or to the back of the **fixing bracket for MAS95 & MAS97 profiles**. Offer the profile to the wall and apply even pressure along the entire length to ensure full contact of the adhesive with the skirting.
5. For details relating to the application of Gradus Grip adhesive, please refer to our dedicated '**Gradus Grip Product Data Sheet – for use with Metal Skirtings**' which provides full installation instructions. This can be downloaded from the Gradus Grip product page at www.gradus.com.
6. To provide a neat finish to cut ends, a range of accessories are also available to order - see below:

MAS90 Aluminium Skirtings – Metal accessories in silver anodised finish:

Skirting Profile	Height	Finish	End Caps	Junction	External Corner	Internal Corner
MAS90/10SF	100mm	Silver	MAS90/10MP	MAS90/10MG	MAS90/10ME	MAS90/10MI
MAS90/8SF	80mm	Silver	MAS90/8MP	MAS90/8MG	MAS90/8ME	MAS90/8MI
MAS90/6SF	60mm	Silver	MAS90/6MP	MAS90/6MG	MAS90/6ME	MAS90/6MI

MSS790 Stainless Steel Skirtings – Metal accessories in satin finish:

Skirting Profile	Height	Finish	End Caps	Junction	External Corner	Internal Corner
MSS790/8SF	80mm	Satin	MSS790/8MPS	MSS790/8MGS	MSS790/8MES	MSS790/8MIS
MSS790/6SF	60mm	Satin	MSS790/6MPS	MSS790/6MGS	MSS790/6MES	MSS790/6MIS

MAS95 Aluminium Interlocking Skirtings – PVC-u accessories in silver finish:

Skirting Profile	Height	Finish	End Caps	Junction	External Corner	Internal Corner
MAS95/10SF	100mm	Silver	MAS95/10P	MAS95/10G	MAS95/10E	MAS95/10I
MAS95/7SF	70mm	Silver	MAS95/7P	MAS95/7G	MAS95/7E	MAS95/7I

MAS97 Aluminium Interlocking Skirting – PVC-u accessories in silver finish:

Skirting Profile	Height	Finish	End Caps	Junction	External Corner	Internal Corner
MAS97/8SF	80mm	Silver	MAS97/8P	MAS97/8G	MAS97/8E	MAS97/8I

Please note - All accessories are supplied in packs of 4, except for End Caps which are supplied as 4 sets of 2 (one left hand and one right hand).

If any further information is required, please contact Gradus Technical Support on +44 (0)1625 428922